

OL 770VIS

Multi-Channel Spectroradiometer Specifications

OL 770VIS Specifications

Wavelength Range (standard)	380 to 780 nm
Wavelength Accuracy	± 0.5 nm
Optical Bandwidth	3.0 nm (with 100 µm input slit minimum binning; 50 µm and 200 µm also available)
Spectral Resolution	± 0.4 nm
Slits (user interchangeable)	100 micron (standard); 50 micron & 200 micron (optional)
Optical Focal Length	140 mm
Optical Input	3 mm Ø X 1 m fiber optic probe
Optical Aperture	f/2
Operating Temperature	0 to 40°C
Operating Humidity	0 to 90% (non-condensing)
Detector Technology	TE-cooled, back-thinned, 2-dimensional CCD array
Detector Cooling Temperature	-10°C
Quantum Efficiency	> 90% at 650 nm
Chromaticity Accuracy	± 0.002 x,y
Chromaticity Repeatability (temperature stabilized blue LED)	± 0.00015 x. ± 0.0002 y
Stray Light (tungsten source)	< 2.5 E ⁻⁴ (> 300 nm)
Integration Time	20 ms – 60 s
A/D Resolution	16 bits
A/D Rate	250 kHz
Power Input	115/230 Vac
Interface	USB, RS-232
Dimensions	W: 7 ¼" (18.4 cm) X H: 13 ¼" (33.6 cm) X D: 13" (33.0 cm)
Weight	22.5 lbs. (10.2 kg)

